

## Project 25 Compliance Assessment Program

SDOC - ICOM – IC-F7510

October 1, 2019

### SUBSCRIBER PRODUCT INFORMATION

Subscriber Info	Detail
Model Name:	IC-F7510
Tested Software Versions:	V3.2 DSP 4.52 / V3.3 DSP 4.53 / V3.31 DSP 4.53
Hardware Capabilities/Options & Software Options:	Full Display; 136–174 MHz P25 Conventional, P25 Trunked, P25 TDMA Trunked, AES-256 Encryption

Test case results and updated software versions for this model can be found in the Summary Test Report identified below.

### TEST REQUIREMENTS CAB IDENTIFICATION

This product was tested according to the P25 CAP Test Requirements Compliance Assessment Bulletin (CAB) indicated by the checked box.

check one	P25 CAP Test Requirement CAB	Details
<input checked="" type="checkbox"/>	<b>P25-CAB-CAI_TEST_REQ – July 2017</b>	Includes August 2016 P25 CAP Test Requirements; Adds TDMA performance and interoperability testing and trunked supplementary data testing
<input type="checkbox"/>	<b>P25-CAB-CAI_TEST_REQ - October 2018</b>	Includes all July 2017 P25 CAP Test Requirements; Adds minor updates to conventional interoperability testing due to TIA standard update

### SUMMARY TEST REPORT IDENTIFIER<sup>1</sup>

Summary Test Report (STR) Identifier:	STR - ICOM – SUBSCRIBER
---------------------------------------	-------------------------

### CONTACT INFORMATION

Vendor Info	Details
Vendor Name:	ICOM AMERICA, INC.
Vendor Website URL:	<a href="http://www.icomamerica.com/">http://www.icomamerica.com/</a>
P25 CAP Contact Name:	MASAAKI TAKAHASHI
P25 CAP Contact Phone:	+1 (425) 450-6073
P25 CAP Contact Email:	<a href="mailto:MasaakiTakahashi@IcomAmerica.com">MasaakiTakahashi@IcomAmerica.com</a>

<sup>1</sup> The Summary Test Report for this product is available upon request. Please send your STR request to [P25CAP@hq.dhs.gov](mailto:P25CAP@hq.dhs.gov) and please include the subscriber 'Vendor Name'.

**Project 25 Compliance Assessment Program**  
**SDOC - ICOM – IC-F7510**  
**October 1, 2019**

**ENCRYPTION STATEMENT**

This product complies with the P25 CAP Encryption Requirements CAB (P25-CAB-ENC\_REQ). The checked box indicates how the product was tested.

<b>X</b>	Tested with the AES 256 encryption algorithm and shall be available with AES 256 encryption at a minimum or without any encryption of any type.
	Tested without the AES 256 encryption algorithm and shall only be available without any encryption of any type.

**CONVENTIONAL PERFORMANCE**

The Subscriber product has been tested for Conventional Performance. All requirements were passed except for those requirements identified below under Unsupported or Failed Requirements.

P25 CAP Conventional Performance Testing Coverage

Receiver Tests: Reference Sensitivity, Faded Reference Sensitivity, Signal Delay Spread Capability, Adjacent Channel Rejection, Offset Adjacent Channel Rejection, Co-Channel Rejection, Spurious Response Rejection, Intermodulation Rejection, Signal Displacement Bandwidth, Late Entry Unsilence Delay, and Receiver Throughput Delay.

Transmitter Tests: Unwanted Emissions (Adjacent Channel Power Ratio), Transmitter Power and Encoder Attack Time, Transmitter Throughput Delay, Frequency Deviation for C4FM, and Modulation Fidelity, Transient Frequency Behavior.

Unsupported or Failed Requirements

1. None

**TRUNKING PERFORMANCE - FDMA**

The Subscriber product has been tested for Trunking Performance - FDMA. All requirements were passed except for those requirements identified below under Unsupported or Failed Requirements.

P25 CAP FDMA Trunking Performance Testing Coverage

Receiver Tests: Reference Sensitivity, Faded Reference Sensitivity, Signal Delay Spread Capability, Adjacent Channel Rejection, Offset Adjacent Channel Rejection, Co-Channel Rejection, Spurious Response Rejection, Intermodulation Rejection, and Signal Displacement Bandwidth.

Transmitter Tests: Unwanted Emissions (Adjacent Channel Power Ratio), Power Attack time, Encoder Attack Time, Transmitter Throughput Delay, Frequency Deviation for C4FM, and Modulation Fidelity, Transient Frequency Behavior.

Trunked Tests: Trunking Control Channel Slot Times, Trunking Request Time, and Transmitter Time to Key on a Traffic Channel.

Unsupported or Failed Requirements

1. None

**Project 25 Compliance Assessment Program**  
**SDOC - ICOM – IC-F7510**  
**October 1, 2019**

**TRUNKING PERFORMANCE - TDMA**

The Subscriber product has been tested for Trunking Performance - TDMA. All requirements were passed except for those requirements identified below under Unsupported or Failed Requirements.

P25 CAP TDMA Trunking Performance Testing Coverage

Receiver Tests: Reference Sensitivity, Faded Reference Sensitivity, Signal Delay Spread Capability, Adjacent Channel Rejection, Offset Adjacent Channel Rejection, Co-Channel Rejection, Spurious Response Rejection, Intermodulation Rejection, and Signal Displacement Bandwidth.

Transmitter Tests: Unwanted Emissions (Adjacent Channel Power Ratio), Frequency Deviation for H-CPM, Modulation Fidelity, Symbol Rate Accuracy, H-CPM Logical Channel Power measurements, and H-CPM Channel Time Alignment.

Unsupported or Failed Requirements

1. None

**CONVENTIONAL DIRECT MODE INTEROPERABILITY**

The Subscriber product has been tested for Conventional Direct Mode Interoperability. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP Direct Mode Interoperability Testing Coverage

Network Access Code (NAC) Operation, Group Voice Call, Emergency Call, Unit-to-Unit Voice Call, Encryption, Call Alert, Radio Check, Message Update, Status Update, Status Query, and Radio Unit Monitor.

Unsupported or Failed Test Cases

1. Radio Unit Monitor – Unit to Unit Call is unsupported

Optional Product Capabilities Required to Pass Test Cases

1. None

**CONVENTIONAL REPEAT MODE INTEROPERABILITY**

The Subscriber product has been tested for Conventional Repeat Mode Interoperability. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP Repeat Mode Interoperability Testing Coverage

Network Access Code (NAC) Operation, Group Voice Call, Emergency Call, Unit-to-Unit Voice Call, Encryption, Call Alert, Radio Check, Message Update, Status Update, Status Query, and Radio Unit Monitor.

**Project 25 Compliance Assessment Program**

**SDOC - ICOM – IC-F7510**

**October 1, 2019**

Unsupported or Failed Test Cases

1. Message Update – SU 1 to Group Message Update is unsupported, Status Update – Test Case 3 – SU to Talk Group Status Update Initiated by SU 1 is unsupported, Radio Unit Monitor – Unit to Unit Call is unsupported

Optional Product Capabilities Required to Pass Test Cases

1. None

**CONVENTIONAL REPEAT MODE with DISPATCH MONITORING CONSOLE INTEROPERABILITY**

The Subscriber product has been tested for Conventional Repeat Mode with Dispatch Monitoring Console Interoperability. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP Repeat Mode Interoperability Testing Coverage

Group Voice Call, Emergency Call, All Call, Unit-to-Unit Voice Call, Encryption, Emergency Alarm, Call Alert, Radio Check, Radio Unit Inhibit/Uninhibit, Message Update, Status Update, Status Query, and Radio Unit Monitor.

Unsupported or Failed Test Cases

1. Message Update – SU 1 to Group Message Update is unsupported, Status Update – Test Case 3 – SU to Talk Group Status Update Initiated by SU 1 is unsupported, Radio Unit Monitor – Unit to Unit Call is unsupported

Optional Product Capabilities Required to Pass Test Cases

1. None

**Project 25 Compliance Assessment Program**  
**SDOC - ICOM – IC-F7510**  
**October 1, 2019**

**TRUNKED SUBSCRIBER UNIT INTEROPERABILITY – FDMA**

The Subscriber product has been tested for Trunked Interoperability - FDMA. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

**P25 CAP FDMA Trunked Interoperability Testing Coverage**

Full Registration, Group Voice Call, Unit to Unit Voice Call, Broadcast Voice Call, Affiliation, Announcement Group Call, Emergency Alarm, Emergency Group Call, Encryption, Intra-Location Registration Area Roaming, Deregistration, System Call, Call Alert, Short Message, Status Query, Status Update, Radio Unit Monitoring, Radio Unit Disable/Re-Enable, and Radio Check.

**Unsupported or Failed Test Cases**

1. Radio Unit Monitoring is unsupported, Inter-System Roaming is unsupported, Inter-WACN Roaming is unsupported
2. Unit-to-Unit Voice Call - Test Case 4 – Unit-to-Unit Call Queued with Target Availability Check – Traffic Channel Assignment Before Target Availability Check and System Call - Functionality is unsupported by the representative base station repeaters/FNEs tested with the subscriber under test

**Optional Product Capabilities Required to Pass Test Cases**

1. None

**TRUNKED SUBSCRIBER UNIT INTEROPERABILITY – TDMA**

The Subscriber product has been tested for Trunked Interoperability - TDMA. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

**P25 CAP TDMA Trunked Interoperability Testing Coverage**

Registration, Group Voice Call, Unit-to-Unit Voice Call, Broadcast Call, Announcement Group Call, Emergency Group Call, Encryption Group Call, System Call, Radio Unit Monitoring, and Transmitting Subscriber Forced Preemption.

**Unsupported or Failed Test Cases**

1. Inter-System Roaming and Inter-WACN Roaming is unsupported.
2. Unit-to-Unit Voice Call - Test Case 5 – Unit-to-Unit Call without Target Availability Check and Test Case 6 – Unit-to-Unit Call Queued without Target Availability Check and Radio Unit Monitoring are unsupported
3. Unit-to-Unit Voice Call - Test Case 4 – Unit-to-Unit Call Queued with Target Availability Check – Traffic Channel Assignment Before Target Availability Check and System Call - Functionality is unsupported by the representative base station repeaters/FNEs tested with the subscriber under test

**Optional Product Capabilities Required to Pass Test Cases**

1. None

Project 25 Compliance Assessment Program  
SDOC - ICOM – IC-F7510  
October 1, 2019

**SIGNATURE AND DATE**

Oct 1, 2019

Date Signed



Vendor's Authorized Representative Signature

Andy Naito

Vendor's Authorized Representative Printed Name

**DISCLAIMER**

The information contained herein has been provided by the supplier of the product with permission to make the information publicly available. The U.S. Department of Homeland Security (DHS) Science and Technology Directorate (S&T) is making this information available as a public service; however, DHS S&T IS PROVIDING THE INFORMATION "AS IS." DHS S&T MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS S&T MAKES NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to any specific commercial products, processes or services by trade name, trademark, supplier, or otherwise does not constitute an endorsement by or a recommendation from DHS S&T.