



**NIJ**

Special

**REPORT**

**Test Results for Hardware Write Block Device:  
Tableau T8 Forensic USB Bridge (USB Interface)**

[www.ojp.usdoj.gov/nij](http://www.ojp.usdoj.gov/nij)

**U.S. Department of Justice  
Office of Justice Programs**

810 Seventh Street N.W.  
Washington, DC 20531

**Michael B. Mukasey**  
*Attorney General*

**Jeffrey L. Sedgwick**  
*Acting Assistant Attorney General*

**David W. Hagy**  
*Director, National Institute of Justice*

This and other publications and products of the National Institute of Justice can be found at:

**National Institute of Justice**  
[www.ojp.usdoj.gov/nij](http://www.ojp.usdoj.gov/nij)

**Office of Justice Programs**  
Innovation • Partnerships • Safer Neighborhoods  
[www.ojp.usdoj.gov](http://www.ojp.usdoj.gov)

**AUG. 08**

**Test Results for Hardware Write Block Device:  
Tableau T8 Forensic USB Bridge (USB Interface)**



**David W. Hagy**

*Director, National Institute of Justice*

This report was prepared for the National Institute of Justice, U.S. Department of Justice, by the Office of Law Enforcement Standards of the National Institute of Standards and Technology under Interagency Agreement 2003-IJ-R-029.

The National Institute of Justice is a component of the Office of Justice Programs, which also includes the Bureau of Justice Assistance, the Bureau of Justice Statistics, the Office of Juvenile Justice and Delinquency Prevention, and the Office for Victims of Crime.

**Test Results for Hardware Write Block Device:  
Tableau T8 Forensic USB Bridge (USB Interface)**

**June 2008**

## Contents

Introduction.....	1
1 Results Summary by Requirements .....	3
2 Test Case Selection .....	4
3 Testing Environment.....	4
3.1 Test Computers .....	4
3.2 Protocol Analyzer .....	4
3.3 Hard Disk Drives .....	4
3.4 Support Software .....	5
4 Test Results .....	5
4.1 Test Results Report Key .....	6
4.2 Test Details .....	7
4.2.1 HWB-01 .....	7
4.2.2 HWB-03-file .....	10
4.2.3 HWB-03-img .....	11
4.2.4 HWB-05 .....	12
4.2.5 HWB-06.....	13
4.2.6 HWB-08.....	14
4.2.7 HWB-09 .....	15

## Introduction

The Computer Forensics Tool Testing (CFTT) program is a joint project of the National Institute of Justice (NIJ), the research and development organization of the U.S. Department of Justice, and the National Institute of Standards and Technology's (NIST's) Office of Law Enforcement Standards, and Information Technology Laboratory. CFTT is supported by other organizations, including the Federal Bureau of Investigation, the U.S. Department of Defense Cyber Crime Center, Internal Revenue Service Criminal Investigation's Electronic Crimes Program, and the U.S. Department of Homeland Security's Bureau of Immigration and Customs Enforcement, U.S. Customs and Border Protection, and U.S. Secret Service. The objective of the CFTT program is to provide measurable assurance to practitioners, researchers, and other applicable users that the tools used in computer forensics investigations provide accurate results. Accomplishing this requires the development of specifications and test methods for computer forensics tools and subsequent testing of specific tools against those specifications.

Test results provide the information necessary for developers to improve tools, users to make informed choices, and the legal community and others to understand the tools' capabilities. This approach to testing computer forensic tools is based on well-recognized methodologies for conformance and quality testing. The specifications and test methods are posted on the CFTT Web site (<http://www.cftt.nist.gov/>) for review and comment by the computer forensics community.

This document reports the results from testing the **Tableau T8 Forensic Bridge (USB Interface)** write blocker, against the *Hardware Write Blocker (HWB) Assertions and Test Plan Version 1.0* and *Hardware Write Blocker Device (HWB) Specification, Version 2.0*, available at the CFTT Web site ([http://www.cftt.nist.gov/hardware\\_write\\_block.htm](http://www.cftt.nist.gov/hardware_write_block.htm)). This specification identifies the following top-level tool requirements:

- A hardware write block (HWB) device shall not transmit a command to a protected storage device that modifies the data on the storage device.
- An HWB device shall return the data requested by a read operation.
- An HWB device shall return without modification any access-significant information requested from the drive.
- Any error condition reported by the storage device to the HWB device shall be reported to the host.

Test results from other software packages can be found on NIJ's computer forensics tool testing web page, <http://www.ojp.usdoj.gov/nij/topics/technology/electronic-crime/cftt.htm>.



# Test Results for Hardware Write Block Devices

Device Tested: Tableau T8 Forensic USB Bridge<sup>1</sup>  
Model: T8  
Serial No: T005A016186,000ecc010008030a  
Firmware: Jul 26 2005 15:01:41

Host to Blocker Interface: USB  
Blocker to Drive Interface: USB

Supplier: Tableau, LLC

Address: N8 W22195 Johnson Drive, Suite 100  
Waukesha, WI 53186  
<http://www.tableau.com/>

## 1 Results Summary by Requirements

- **An HWB device shall not transmit a command to a protected storage device that modifies the data on the storage device.**  
For all test cases run, the device always blocked any commands that would have changed user or operating system data stored on a protected drive.
- **An HWB device shall return the data requested by a read operation.**  
For all test cases run, the device always allowed commands to read the protected drive.
- **An HWB device shall return without modification any access-significant information requested from the drive.**  
For all test cases run, the device always returned access-significant information from the protected drive without modification.
- **Any error condition reported by the storage device to the HWB device shall be reported to the host.**  
For all test cases run, the device always returned error codes from the protected drive without modification.

---

<sup>1</sup> Tableau produces this write block device for resale under various partner labels. See <http://www.tableau.com> for information on resellers.

## 2 Test Case Selection

Since a protocol analyzer was available for the interface between the blocker and the protected drive, the following test cases were appropriate:

- HWB-01
- HWB-03
- HWB-05
- HWB-06
- HWB-08
- HWB-09

For test case HWB-03, two variations were selected: file (attempt to use operating system commands to create and delete files and directories from a protected drive) and image (use an imaging tool to attempt to write to a protected drive).

## 3 Testing Environment

The tests were run in the NIST CFTT lab. This section describes the hardware (test computers and hard drives) available for testing.

### 3.1 Test Computers

One test computer, **JohnSteed**, with the following configuration was used:

Intel® Desktop Motherboard FIC IC-VL67 (865G; S478; 800MHz)  
BIOS Phoenix Award version v6.00PG  
Intel® Pentium™ 4 CPU  
Plextor DVDR PX-716A, ATAPI CD/DVD-ROM Drive  
Western Digital Corporation WD800JB-00JJC0, 80 GB ATA disk drive  
1.44 MB floppy drive  
Three IEEE 1394 ports  
Four USB ports

### 3.2 Protocol Analyzer

A Data Transit bus protocol analyzer (Bus Doctor Rx) was used to monitor and record commands sent from the host to the write blocker. Two identical protocol analyzers were available for monitoring commands.

One of two Dell laptop computers (either **Chip** or **Dale**) was connected to each protocol analyzer to record commands observed by the protocol analyzer.

### 3.3 Hard Disk Drives

Two USB interface devices were used in testing:

- 48-u12 is a Maxtor 3000LS with 80293248 sectors (40 GB).
- D4-thumb is a USB flash memory drive.

Drive label: 48-U12							
80293248 total number of sectors							
Non-IDE disk							
Model (F040L0)							
N	Start	LBA	Length	Start C/H/S	End C/H/S	boot	Partition type
1	X	000016065	080276805	0001/000/01	1023/254/63	0F	extended
2	S	000000063	000032067	0001/001/01	0002/254/63	01	Fat12
3	x	000032130	000080325	0003/000/01	0007/254/63	05	extended
4	S	000000063	000080262	0003/001/01	0007/254/63	0B	Fat32
5	x	000112455	002345490	0008/000/01	0153/254/63	05	extended
6	S	000000063	002345427	0008/001/01	0153/254/63	07	NTFS
7	S	000000000	000000000	0000/000/00	0000/000/00	00	empty entry
8	P	000000000	000000000	0000/000/00	0000/000/00	00	empty entry
9	P	000000000	000000000	0000/000/00	0000/000/00	00	empty entry
10	P	000000000	000000000	0000/000/00	0000/000/00	00	empty entry
Drive label: d4-thumb							
505856 total number of sectors							
Model (usb2.0Flash Disk)							

### 3.4 Support Software

The software in the following table was used to send commands to the protected drive. One widely used imaging tool, IXimager, was used to generate disk activity (reads and writes) consistent with a realistic scenario of an accidental modification of an unprotected hard drive during a forensic examination. This does not imply an endorsement of the imaging tool.

Program	Description
sendSCSI	A tool to send SCSI commands wrapped in the USB or IEEE 1394 (FireWire) protocols to a drive.
FS-TST	Software from the FS-TST tools was used to generate errors from the hard drive by trying to read beyond the end of the drive. The FS-TST software was also used to setup the hard drives and print partition tables and drive size.
IXimager	An imaging tool (ILook IXimager version 1.0, August 25, 2004) for test case 04-img.

## 4 Test Results

The main item of interest for interpreting the test results is determining the conformance of the device with the test assertions. Conformance with each assertion tested by a given test case is evaluated by examining the Blocker Input and Blocker Output boxes of the test report summary.

## 4.1 Test Results Report Key

A summary of the actual test results is presented in this report. The following table presents a description of each section of the test report summary.

<b>Heading</b>	<b>Description</b>
First Line	Test case ID; name, model, and interface of device tested.
Case Summary	Test case summary from <i>Hardware Write Blocker (HWB) Assertions and Test Plan Version 1.0</i> .
Assertions Tested	The test assertions applicable to the test case, selected from <i>Hardware Write Blocker (HWB) Assertions and Test Plan Version 1.0</i> .
Tester Name	Name or initials of person executing test procedure.
Test Date	Time and date that test was started and completed.
Test Configuration	Identification of the following: <ol style="list-style-type: none"> <li>1. Host computer for executing the test case.</li> <li>2. Laptop attached to each protocol analyzer.</li> <li>3. Protocol analyzers monitoring each interface.</li> <li>4. Interface between host and blocker.</li> <li>5. Interface between blocker and protected drive.</li> <li>6. Execution environment for tool sending commands from the host.</li> </ol>
Hard Drives Used	Description of the protected hard drive.
Blocker Input	A list of commands sent from the host to the blocker.  For test case HWB–01, a list of each command code observed on the bus between the blocker and the protected drive and a count of the number of times the command was observed is provided.  For test cases HWB–03 and HWB–06, a list of each command sent and the number of times the command was sent.  For test case HWB–05, a string of known data from a given location is provided for reference.
Blocker Output	A list of commands observed by the protocol analyzer on the bus from the blocker to the protected drive.  For test case HWB–01, a list of each command code observed on the bus between the blocker and the protected drive and a count of the number of times the command was observed is provided. Also, a count of the number of unique commands sent (from the Blocker Input box) and a count of the number of unique commands observed on the bus

Heading	Description
	<p>between the blocker and the protected drive.</p> <p>For test cases HWB-03 and HWB-06, a list of each command sent and the number of times the command was sent.</p> <p>For test case HWB-05, a string read from a given location is provided for comparison to known data.</p> <p>For test case HWB-08, the number of sectors determined for the protected drive and the partition table are provided.</p> <p>For test case HWB-09, any error return obtained by trying to access a nonexistent sector of the drive is provided.</p>
Results	Expected and actual results for each assertion tested.
Analysis	Whether or not the expected results were achieved.

## 4.2 Test Details

### 4.2.1 HWB-01

Test Case HWB-01 Variation hwb-01 Tableau T8 USB																			
Case Summary:	HWB-01 Identify commands blocked by the HWB.																		
Assertions Tested:	<p>HWB-AM-01 The HWB shall not transmit any modifying category operation to the protected storage device.</p> <p>HWB-AM-05 The action that a HWB device takes for any commands not assigned to the modifying, read or information categories is defined by the vendor.</p>																		
Tester Name:	rpa																		
Test Date:	<p>run start Wed Apr 4 13:54:43 2007</p> <p>run finish Thu Apr 5 10:34:41 2007</p>																		
Test Configuration:	<p>HOST: johnsteed</p> <p>HostToBlocker Monitor: dale</p> <p>HostToBlocker PA: aa00111</p> <p>HostToBlocker Interface: usb</p> <p>BlockerToDrive Monitor: chip</p> <p>BlockerToDrive PA: aa00155</p> <p>BlockerToDrive Interface: usb</p> <p>Run Environment: linux</p>																		
Drives:	<p>Protected drive: 48-u12</p> <p>48-u12 is a Maxtor 3000LS with 80293248 sectors (40 GB)</p>																		
Blocker Input:	<p>Commands Sent to Blocker</p> <table border="1" data-bbox="467 1654 781 1877"> <thead> <tr> <th>Count</th> <th>Commands</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>BLANK</td> </tr> <tr> <td>1</td> <td>CHG</td> </tr> <tr> <td>1</td> <td>CLOS</td> </tr> <tr> <td>1</td> <td>COMPARE</td> </tr> <tr> <td>1</td> <td>COPY</td> </tr> <tr> <td>1</td> <td>COPY/VERIFY</td> </tr> <tr> <td>1</td> <td>ERASE</td> </tr> <tr> <td>1</td> <td>ERASE(10)</td> </tr> </tbody> </table>	Count	Commands	1	BLANK	1	CHG	1	CLOS	1	COMPARE	1	COPY	1	COPY/VERIFY	1	ERASE	1	ERASE(10)
Count	Commands																		
1	BLANK																		
1	CHG																		
1	CLOS																		
1	COMPARE																		
1	COPY																		
1	COPY/VERIFY																		
1	ERASE																		
1	ERASE(10)																		

Test Case HWB-01 Variation hwb-01 Tableau T8 USB

	1	FORMAT
	3	GET
	1	INQUIRY
	1	LK/UNLK
	1	LOAD/UNLOAD
	2	LOG
	1	MECH
	1	MEDIUM
	4	MODE
	1	PAUSE/RESUME
	2	PERSISTENT
	5	PLAY
	2	PLY
	1	PRE-FETCH
	1	PREVENT/ALLOW
	7	RD
	13	READ
	547	READ(10)
	1	READ(12)
	1	REASSIGN
	1	RECEIVE
	1	RECIEVE(6)
	1	RECOVER
	1	RELEASE(10)
	1	RELEASE(6)
	1	REPAIR
	5	REPORT
	1	REQ
	232	REQUEST_SENSE
	1	RESERVE(10)
	1	RESERVE(6)
	1	REZERO
	65	Reserved
	1	SCAN
	1	SEEK(10)
	1	SEEK(6)
	9	SEND
	1	SEND(6)
	4	SET
	1	SND
	1	SPACE
	6	SRCH
	1	START/STOP
	1	STOP
	1	SYNCH
	1	TEST
	1	UPDATE
	1	VERIFY
	1	VERIFY(12)
	1	VERIFY(6)
	5	WRITE
	1	WRITE(10)
	1	WRITE(12)
	1	WRITE/VERIFY
	1	XDREAD(10)
	1	XDWRITE(10)
	1	XDWRITEREAD(10)
	1	XPWRITE(10)
	66 commands sent	

Blocker Output:	Commands Allowed by Blocker						
	<table border="1"> <thead> <tr> <th>Count</th> <th>Commands</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>PREVENT/ALLOW</td> </tr> <tr> <td>547</td> <td>READ(10)</td> </tr> </tbody> </table>	Count	Commands	1	PREVENT/ALLOW	547	READ(10)
Count	Commands						
1	PREVENT/ALLOW						
547	READ(10)						

Test Case HWB-01 Variation hwb-01 Tableau T8 USB		
	1	REQUEST_SENSE
	1	START/STOP
	1	SYNCH
	1	TEST
	1	VERIFY
66 commands sent, 7 commands allowed		
Results:	<b>Assertion &amp; Expected Result</b>	<b>Actual Result</b>
	AM-01 Modifying commands blocked	Modifying commands blocked
	AM-05 HWB behavior recorded	HWB behavior recorded
Analysis:	Expected results achieved	

## 4.2.2 HWB-03-file

Test Case HWB-03 Variation hwb-03-file Tableau T8 USB													
Case Summary:	HWB-03 Identify commands blocked by the HWB while attempting to modify a protected drive with forensic tools.												
Assertions Tested:	HWB-AM-01 The HWB shall not transmit any modifying category operation to the protected storage device. HWB-AM-05 The action that a HWB device takes for any commands not assigned to the modifying, read or information categories is defined by the vendor.												
Tester Name:	rpa												
Test Date:	run start Thu Apr 5 14:20:28 2007 run finish Mon Apr 9 10:06:34 2007												
Test Configuration:	HOST: johnsteeed HostToBlocker Monitor: dale HostToBlocker PA: aa00111 HostToBlocker Interface: usb BlockerToDrive Monitor: chip BlockerToDrive PA: aa00155 BlockerToDrive Interface: usb Run Environment: DOS												
Drives:	Protected drive: 48-u12 48-u12 is a Maxtor 3000LS with 80293248 sectors (40 GB)												
Blocker Input:	Commands Sent to Blocker <table border="1"> <thead> <tr> <th>Count</th> <th>Commands</th> </tr> </thead> <tbody> <tr> <td>7</td> <td>MODE</td> </tr> <tr> <td>14</td> <td>READ</td> </tr> <tr> <td>592</td> <td>READ(10)</td> </tr> <tr> <td>124</td> <td>REQUEST_SENSE</td> </tr> <tr> <td>162</td> <td>TEST</td> </tr> </tbody> </table>	Count	Commands	7	MODE	14	READ	592	READ(10)	124	REQUEST_SENSE	162	TEST
Count	Commands												
7	MODE												
14	READ												
592	READ(10)												
124	REQUEST_SENSE												
162	TEST												
Blocker Output:	Commands Allowed by Blocker <table border="1"> <thead> <tr> <th>Count</th> <th>Commands</th> </tr> </thead> <tbody> <tr> <td>592</td> <td>READ(10)</td> </tr> <tr> <td>7</td> <td>TEST</td> </tr> </tbody> </table>	Count	Commands	592	READ(10)	7	TEST						
Count	Commands												
592	READ(10)												
7	TEST												
Results:	<table border="1"> <thead> <tr> <th>Assertion &amp; Expected Result</th> <th>Actual Result</th> </tr> </thead> <tbody> <tr> <td>AM-01 Modifying commands blocked</td> <td>Modifying commands blocked</td> </tr> <tr> <td>AM-05 HWB behavior recorded</td> <td>HWB behavior recorded</td> </tr> </tbody> </table>	Assertion & Expected Result	Actual Result	AM-01 Modifying commands blocked	Modifying commands blocked	AM-05 HWB behavior recorded	HWB behavior recorded						
Assertion & Expected Result	Actual Result												
AM-01 Modifying commands blocked	Modifying commands blocked												
AM-05 HWB behavior recorded	HWB behavior recorded												
Analysis:	Expected results achieved												

### 4.2.3 HWB-03-img

Test Case HWB-03 Variation hwb-03-img Tableau T8 USB							
Case Summary:	HWB-03 Identify commands blocked by the HWB while attempting to modify a protected drive with forensic tools.						
Assertions Tested:	HWB-AM-01 The HWB shall not transmit any modifying category operation to the protected storage device. HWB-AM-05 The action that a HWB device takes for any commands not assigned to the modifying, read or information categories is defined by the vendor.						
Tester Name:	rpa						
Test Date:	run start Mon Apr 9 11:28:15 2007 run finish Mon Apr 9 14:05:55 2007						
Test Configuration:	HOST: johnsteeed HostToBlocker Monitor: dale HostToBlocker PA: aa00111 HostToBlocker Interface: usb BlockerToDrive Monitor: chip BlockerToDrive PA: aa00155 BlockerToDrive Interface: usb Run Environment: IX						
Drives:	Protected drive: D4-thumB						
Blocker Input:	Commands Sent to Blocker <table border="1"> <thead> <tr> <th>Count</th> <th>Commands</th> </tr> </thead> <tbody> <tr> <td>5</td> <td>READ(10)</td> </tr> <tr> <td>11</td> <td>TEST</td> </tr> </tbody> </table>	Count	Commands	5	READ(10)	11	TEST
Count	Commands						
5	READ(10)						
11	TEST						
Blocker Output:	Commands Allowed by Blocker <table border="1"> <thead> <tr> <th>Count</th> <th>Commands</th> </tr> </thead> <tbody> <tr> <td>5</td> <td>READ(10)</td> </tr> <tr> <td>11</td> <td>TEST</td> </tr> </tbody> </table>	Count	Commands	5	READ(10)	11	TEST
Count	Commands						
5	READ(10)						
11	TEST						
Results:	<table border="1"> <thead> <tr> <th>Assertion &amp; Expected Result</th> <th>Actual Result</th> </tr> </thead> <tbody> <tr> <td>AM-01 Modifying commands blocked</td> <td>Modifying commands blocked</td> </tr> <tr> <td>AM-05 HWB behavior recorded</td> <td>HWB behavior recorded</td> </tr> </tbody> </table>	Assertion & Expected Result	Actual Result	AM-01 Modifying commands blocked	Modifying commands blocked	AM-05 HWB behavior recorded	HWB behavior recorded
Assertion & Expected Result	Actual Result						
AM-01 Modifying commands blocked	Modifying commands blocked						
AM-05 HWB behavior recorded	HWB behavior recorded						
Analysis:	Expected results achieved						

## 4.2.4 HWB-05

Test Case HWB-05 Variation hwb-05 Tableau T8 USB					
Case Summary:	HWB-05 Identify read commands allowed by the HWB.				
Assertions Tested:	HWB-AM-02 If the host sends a read category operation to the HWB and no error is returned from the protected storage device to the HWB, then the data addressed by the original read operation is returned to the host.				
Tester Name:	rpa				
Test Date:	run start Wed Apr 11 10:38:39 2007 run finish Wed Apr 11 10:43:35 2007				
Test Configuration:	HOST: johnsteed HostToBlocker Monitor: dale HostToBlocker PA: aa00111 HostToBlocker Interface: usb BlockerToDrive Monitor: none BlockerToDrive PA: none BlockerToDrive Interface: usb Run Environment: linux				
Drives:	Protected drive: 48-u12 48-u12 is a Maxtor 3000LS with 80293248 sectors (40 GB)				
Blocker Input:	Commands Sent to Blocker Read sector 32767 for the string: 00002/010/08 000000032767				
Blocker Output:	00002/010/08 000000032767				
Results:	<table border="1"> <thead> <tr> <th>Assertion &amp; Expected Result</th> <th>Actual Result</th> </tr> </thead> <tbody> <tr> <td>AM-02 Read commands allowed</td> <td>Read commands allowed</td> </tr> </tbody> </table>	Assertion & Expected Result	Actual Result	AM-02 Read commands allowed	Read commands allowed
Assertion & Expected Result	Actual Result				
AM-02 Read commands allowed	Read commands allowed				
Analysis:	Expected results achieved				

## 4.2.5 HWB-06

Test Case HWB-06 Variation hwb-06-img Tableau T8 USB									
Case Summary:	HWB-06 Identify read and information commands used by forensic tools and allowed by the HWB.								
Assertions Tested:	<p>HWB-AM-02 If the host sends a read category operation to the HWB and no error is returned from the protected storage device to the HWB, then the data addressed by the original read operation is returned to the host.</p> <p>HWB-AM-03 If the host sends an information category operation to the HWB and if there is no error on the protected storage device, then any returned access-significant information is returned to the host without modification.</p> <p>HWB-AM-05 The action that a HWB device takes for any commands not assigned to the modifying, read or information categories is defined by the vendor.</p>								
Tester Name:	rpa								
Test Date:	run start Wed Apr 11 11:02:37 2007 run finish Wed Apr 11 11:45:15 2007								
Test Configuration:	HOST: johnsteed HostToBlocker Monitor: dale HostToBlocker PA: aa00111 HostToBlocker Interface: usb BlockerToDrive Monitor: chip BlockerToDrive PA: aa00155 BlockerToDrive Interface: usb Run Environment: IX								
Drives:	Protected drive: D4-thumB								
Blocker Input:	Commands Sent to Blocker <table border="1" data-bbox="467 999 691 1104"> <thead> <tr> <th>Count</th> <th>Commands</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>INQUIRY</td> </tr> <tr> <td>9</td> <td>READ(10)</td> </tr> <tr> <td>21</td> <td>TEST</td> </tr> </tbody> </table> <p>3 commands sent</p>	Count	Commands	2	INQUIRY	9	READ(10)	21	TEST
Count	Commands								
2	INQUIRY								
9	READ(10)								
21	TEST								
Blocker Output:	Commands Allowed by Blocker <table border="1" data-bbox="467 1226 691 1304"> <thead> <tr> <th>Count</th> <th>Commands</th> </tr> </thead> <tbody> <tr> <td>9</td> <td>READ(10)</td> </tr> <tr> <td>21</td> <td>TEST</td> </tr> </tbody> </table> <p>3 commands sent, 2 commands allowed</p>	Count	Commands	9	READ(10)	21	TEST		
Count	Commands								
9	READ(10)								
21	TEST								
Results:	<table border="1" data-bbox="467 1402 1385 1528"> <thead> <tr> <th>Assertion &amp; Expected Result</th> <th>Actual Result</th> </tr> </thead> <tbody> <tr> <td>AM-02 Read commands allowed</td> <td>Read commands allowed</td> </tr> <tr> <td>AM-03 Access Significant Information unaltered</td> <td>Access Significant Information unaltered</td> </tr> <tr> <td>AM-05 HWB behavior recorded</td> <td>HWB behavior recorded</td> </tr> </tbody> </table>	Assertion & Expected Result	Actual Result	AM-02 Read commands allowed	Read commands allowed	AM-03 Access Significant Information unaltered	Access Significant Information unaltered	AM-05 HWB behavior recorded	HWB behavior recorded
Assertion & Expected Result	Actual Result								
AM-02 Read commands allowed	Read commands allowed								
AM-03 Access Significant Information unaltered	Access Significant Information unaltered								
AM-05 HWB behavior recorded	HWB behavior recorded								
Analysis:	Expected results achieved								

## 4.2.6 HWB-08

Test Case HWB-08 Variation hwb-08 Tableau T8 USB					
Case Summary:	HWB-08 Identify access significant information unmodified by the HWB.				
Assertions Tested:	HWB-AM-03 If the host sends an information category operation to the HWB and if there is no error on the protected storage device, then any returned access-significant information is returned to the host without modification.				
Tester Name:	rpa				
Test Date:	run start Wed Apr 11 14:18:24 2007 run finish Wed Apr 11 14:23:26 2007				
Test Configuration:	HOST: johnsteed HostToBlocker Monitor: none HostToBlocker PA: none HostToBlocker Interface: usb BlockerToDrive Monitor: none BlockerToDrive PA: none BlockerToDrive Interface: usb Run Environment: linux				
Drives:	Protected drive: 48-u12 48-u12 is a Maxtor 3000LS with 80293248 sectors (40 GB)				
Blocker Output:	cmd: /mnt/floppy/partab hwb-08 johnsteed rpa /dev/sda -all 80293248 total number of sectors				
Results:	<table border="1"> <thead> <tr> <th>Assertion &amp; Expected Result</th> <th>Actual Result</th> </tr> </thead> <tbody> <tr> <td>AM-03 Access Significant Information unaltered</td> <td>Access Significant Information unaltered</td> </tr> </tbody> </table>	Assertion & Expected Result	Actual Result	AM-03 Access Significant Information unaltered	Access Significant Information unaltered
	Assertion & Expected Result	Actual Result			
AM-03 Access Significant Information unaltered	Access Significant Information unaltered				
Analysis:	Expected results achieved				

## 4.2.7 HWB-09

Test Case HWB-09 Variation hwb-09 Tableau T8 USB					
Case Summary:	HWB-09 Determine if an error on the protected drive is returned to the host.				
Assertions Tested:	HWB-AM-04 If the host sends an operation to the HWB and if the operation results in an unresolved error on the protected storage device, then the HWB shall return an error status code to the host.				
Tester Name:	rpa				
Test Date:	run start Wed Apr 11 14:26:43 2007 run finish Wed Apr 11 14:50:14 2007				
Test Configuration:	HOST: johnsteed HostToBlocker Monitor: none HostToBlocker PA: none HostToBlocker Interface: usb BlockerToDrive Monitor: none BlockerToDrive PA: none BlockerToDrive Interface: usb Run Environment: linux				
Drives:	Protected drive: 48-u12 48-u12 is a Maxtor 3000LS with 80293248 sectors (40 GB)				
Blocker Output:	04997/254/63 (max cyl/hd values) 04998/255/63 (number of cyl/hd) 80293248 total number of sectors cmd: /mnt/floppy/diskchg hwb-09 johnsteed rpa /dev/sda -read 90293248 0 2 Disk addr lba 90293248 C/H/S 5620/126/11 offset 0 Disk read error 0xFFFFFFFF at sector 5620/126/11				
Results:	<table border="1"> <thead> <tr> <th>Assertion &amp; Expected Result</th> <th>Actual Result</th> </tr> </thead> <tbody> <tr> <td>AM-04 Error code returned</td> <td>Error code returned</td> </tr> </tbody> </table>	Assertion & Expected Result	Actual Result	AM-04 Error code returned	Error code returned
Assertion & Expected Result	Actual Result				
AM-04 Error code returned	Error code returned				
Analysis:	Expected results achieved				

## About the National Institute of Justice

NIJ is the research, development, and evaluation agency of the U.S. Department of Justice. NIJ's mission is to advance scientific research, development, and evaluation to enhance the administration of justice and public safety. NIJ's principal authorities are derived from the Omnibus Crime Control and Safe Streets Act of 1968, as amended (see 42 U.S.C. §§ 3721–3723).

The NIJ Director is appointed by the President and confirmed by the Senate. The Director establishes the Institute's objectives, guided by the priorities of the Office of Justice Programs, the U.S. Department of Justice, and the needs of the field. The Institute actively solicits the views of criminal justice and other professionals and researchers to inform its search for the knowledge and tools to guide policy and practice.

### Strategic Goals

NIJ has seven strategic goals grouped into three categories:

#### Creating relevant knowledge and tools

1. Partner with State and local practitioners and policymakers to identify social science research and technology needs.
2. Create scientific, relevant, and reliable knowledge—with a particular emphasis on terrorism, violent crime, drugs and crime, cost-effectiveness, and community-based efforts—to enhance the administration of justice and public safety.
3. Develop affordable and effective tools and technologies to enhance the administration of justice and public safety.

#### Dissemination

4. Disseminate relevant knowledge and information to practitioners and policymakers in an understandable, timely, and concise manner.
5. Act as an honest broker to identify the information, tools, and technologies that respond to the needs of stakeholders.

#### Agency management

6. Practice fairness and openness in the research and development process.
7. Ensure professionalism, excellence, accountability, cost-effectiveness, and integrity in the management and conduct of NIJ activities and programs.

### Program Areas

In addressing these strategic challenges, the Institute is involved in the following program areas: crime control and prevention, including policing; drugs and crime; justice systems and offender behavior, including corrections; violence and victimization; communications and information technologies; critical incident response; investigative and forensic sciences, including DNA; less-than-lethal technologies; officer protection; education and training technologies; testing and standards; technology assistance to law enforcement and corrections agencies; field testing of promising programs; and international crime control.

In addition to sponsoring research and development and technology assistance, NIJ evaluates programs, policies, and technologies. NIJ communicates its research and evaluation findings through conferences and print and electronic media.

To find out more about the National Institute of Justice, please visit:

<http://www.ojp.usdoj.gov/nij>

or contact:

National Criminal Justice  
Reference Service  
P.O. Box 6000  
Rockville, MD 20849-6000  
800-851-3420  
<http://www.ncjrs.gov>